



Gallon per Minute

Drain Water	10.59 US gal.	40.1 Liters/min.
Tap Water In	3.17 US gal.	12 Liters/min.
Top Showerhead	3.17 US gal.	12 Liters/min.
Movable Hand Showerhead	3.17 US gal.	12 Liters/min.
Back-wall body Jets	4.5 US gal.	17.03 Liters/min.
Whirlpool big Massage Jets	70.45 US gal.	266.65 Liters/min.
Whirlpool Bubble Bath Jets	46.24 US gal.	175 Liters/min.

WHIRLPOOL BATH VIEW

Technical Specifications

G168

Products Dimension

L1430 x D1430 x H2220mm
(L56.3" x D56.3" x H87.4")

Products Weight

Box A: 86 KGS (189 lb)
Box B: 125 KGS (275 lb)

Shipping Weight

Box A: 132 KGS (290 lb)
Box B: 165 KGS (363 lb)

Package Dimension

Box A: 1580 x 820 x 790mm(62"x 32" x 31")
Box B: 1570 x 1570 x 700mm(61.8" x 61.8" x 27.5")

Electrical Specifications

2 Water pumps:1460W/110V/60Hz/13.3Amps
Steam Generator: 3000W/110V/60Hz/27.3Amps
Heater(Optional): already included in Steam Generator

Number of Jets

14 pcs body massage jets
24 pcs whirlpool bubble bath jets
6 big whirlpool massage jets

Whirlpool Water Capacity

800~950 Litters (210~250 US gal.)

Minimum Working Water Pressure

4.0 bar (57.14 psi)

Maximum Working Water Pressure

8.0 bar (114.29 psi)

Recommended Working Water Pressure

6.0 bar (85.72 psi)

Minimum Working Water Temperature

5° C (41° F)

Maximum Working Water Temperature

60° C (140° F)

Minimum Working Water Temperature

37° C (98° F)

Size of drainage pipe

φ 35mm (1.38")

MP3/MP4 compatible (Optional)