



Gallon per Minute

| | | |
|-------------------------|--------------|------------------|
| Drain Water | 8.98 US gal. | 34 Liters/min. |
| Top Showerhead | 3.18 US gal. | 12 Liters/min. |
| Movable Hand Showerhead | 3.18 US gal. | 12 Liters/min. |
| Back-wall body Jets | 5.5 US gal. | 20.4 Liters/min. |

Water Pressure is 0.4~0.6Mpa.

Technical Specifications

G267-G167A

Products Dimension

L950 x D950 x H2200mm
(L31.4" x D31.4" x H86.6")

Products Weight

Box A: 99 KGS (218 lb)
Box B: 22 KGS (49 lb)

Shipping Weight

Box A: 150 KGS (330 lb)
Box B: 40 KGS (88 lb)

Package Dimension

Box A: 1970 x 600 x 570mm (41.5"x23.6"x62.4")
Box B: 1000 x 1000 x 360mm (33.3"x33.3"x14.1")

Electrical Specifications

Steam Generator: 3000W/110V/60Hz/27.3Amps

Number of Jets

4 body massage jets

Minimum Working Water Pressure

4.0 bar (57.14 psi)

Maximum Working Water Pressure

8.0 bar (114.29 psi)

Recommended Working Water Pressure

6.0 bar (85.72 psi)

Minimum Working Water Temperature

5° C (41° F)

Maximum Working Water Temperature

60° C (140° F)

Minimum Working Water Temperature

37° C (98° F)

Size of drainage pipe

φ 35mm (1.38")