



Gallon per Minute

Drain Water	8.98 US gal.	34 Liters/min.
Top Showerhead	3.18 US gal.	12 Liters/min.
Movable Hand Showerhead	3.18 US gal.	12 Liters/min.
Back-wall body Jets	16.1 US gal.	61.2 Liters/min.

Water Pressure is 0.4~0.6Mpa.

Technical Specifications

G268

Products Dimension

L1400 x D930x H2200mm
(L55" x D36.6" x H86.61")

Products Weight

Box A: 50 KGS (110 lb)
Box B: 92 KGS (203 lb)

Shipping Weight

Box A: 88 KGS (194 lb)
Box B: 135 KGS (297 lb)

Package Dimension

Box A: 1460 x 950 x 300mm (57"x37"x12")
Box B: 1960 x 1400 x 560mm (77"x55"x22")

Electrical Specifications

Steam Generator: 3000W/110V/60Hz/27.3Amps

Number of Jets

16 body massage jets

Minimum Working Water Pressure

4.0 bar (57.14 psi)

Maximum Working Water Pressure

8.0 bar (114.29 psi)

Recommended Working Water Pressure

6.0 bar (85.72 psi)

Minimum Working Water Temperature

5° C (41° F)

Maximum Working Water Temperature

60° C (140° F)

Minimum Working Water Temperature

37° C (98° F)

Size of drainage pipe

φ 35mm (1.38")